

Technical Manual

No. 5-811-7

HEADQUARTERS
DEPARTMENT OF THE ARMY
WASHINGTON, D.C. 22 April 1985

ELECTRICAL DESIGN, CATHODIC PROTECTION

	<i>Paragraph</i>	<i>Page</i>
CHAPTER 1. INTRODUCTION TO CATHODIC PROTECTION		
Purpose	1-1	1-1
References	1-2	1-1
Corrosion	1-3	1-1
Cathodic protection	1-5	1-1
Types of cathodic protection systems		
2. CATHODIC PROTECTION DESIGN		
Required information	2-1	2-1
Determining the type and design of cathodic protection system	2-2	2-3
APPENDIX A SOIL RESISTIVITY MEASUREMENT		A-1
B CURRENT REQUIREMENT TESTING		B-1
C EXAMPLES OF GALVANIC CATHODIC PROTECTION DESIGN		C-1
D EXAMPLES OF IMPRESSED CURRENT CATHODIC PROTECTION DESIGN		D-1
E SPECIFICATIONS FOR CERAMIC ANODE		E-1
F RECTIFIER CURRENT INTERFERENCE		F-1
BIBLIOGRAPHY		BIBLIO-1
GLOSSARY		GLOSS-1

LIST OF FIGURES

<i>Figure</i>		<i>Page</i>
1-1	Corrosion of a pipeline due to localized anode and cathode sites	1-1
1-2.	Galvanic and impressed current systems for cathodic protection	1-2
2-1.	Design sequence for cathodic protection systems	2-3
A-1.	Wenner four-pin method for measuring resistivity	A-1
A-2.	Soil box for soil resistivity measurements	A-2
B-1.	Current requirement test on pipelines	B-1
C-1.	Galvanic anode cathodic protection for hydrant refueling system	C-1
C-2.	Galvanic anode cathodic protection for underground steel storage tank	C-4
C-5.	Layout of gas piping in residential district	C-5
D-1.	Cathodic protection system for gas main	D-1
D-2.	Impressed current cathodic protection for heating conduit system	D-4
D-3.	Cathodic protection for black iron hot water storage tank	D-7
D-4.	Fringe factor for stub anodes	D-9
D-5.	Dimensions for an elevated steel water tank	D-10
D-6.	Cathodic protection for tanks using rigid-mounted button-type anodes and platinized titanium wire	D-12
D-7.	Segmented elevated tank for area calculations	D-13
D-8.	Anode spacing for elevated steel water tank	D-15
D-9.	Anode suspension arrangement for elevated steel water tank	D-17
D-10.	Equivalent diameter factor for anodes in a circule in water tank	D-18

This manual supersedes Sections VII, VIII, and IX of TM 5-811-4, 1 August 1962.

LIST OF FIGURES (CONT'd)

	<i>Paragraph</i>	<i>Page</i>
D-1.1. Elevated steel water tank showing rectifier and anode arrangement	D-24	
D-12. Hand hole and anode suspension detail for elevated water tank	9-25	
D-13. Riser anode suspension detail for elevated water tank	9-25	
E-1. Ceramic anode specifications	E-1	
F-1. Structure-to-soil potential versus distance from foreign structure	F-1	
F-2. Cathodic interference testing	F-2	

LIST OF TABLES

<i>Table</i>		<i>Page</i>
2-1. Corrosivity of soils on steel based on soil resistivity	2-1	
2-2. Typical current density requirements for cathodic protection of uncoated steel	2-2	
2-3. Weights and dimensions of selected high-potential magnesium-alloy anodes	2-4	
2-4. Weights and dimensions of selected circular high-silicon chromium-bearing cast iron anodes	2-6	
2-5. Shape functions (K) for impressed current cathodic protection anodes where L is the effective anode length and d is the anode/backfill diameter	2-6	
2-6. Anode paralleling factors (P) for various numbers of anodes (N) installed in parallel	2-6	
C-1. Outside area of liquid fuel pipes	C-2	
C-2. Requirements for anode spacing	C-5	
C-3. Dimensions for finding outside area of pipe	C-6	
C-4. Galvanic anode size factor If)	C-7	
C-5. Structure potential factor (y)	C-7	
C-6. Dimensions for finding anode division	C-8	
D-1. Dimensions for finding steam conduit area: heat distribution system	D-5	
D-2. Dimensions for finding condensate return conduit area: heat distribution system	D-5	
D-3. Conduit area: heat distribution system	D-6	
D-4. Anode division: heat distribution system	D-7	
D-5. Technical data: commonly used HSCBCI anodes	D-1	